SHAPE 50



Product Sheet

Shape 50 is the ultimate all-round studio monitor. This monitor can be used from 30" away (80cm), and it has very extended low end frequency response (50Hz) considering its compact design. Thanks to this design and to the numerous settings, this monitor is ideal for rooms measuring less than 130ft² (12m²).



Key points

- Low directivity tweeter for a flexible listening position
- Designed without a port allowing it to be placed near a wall
- Numerous settings for optimal integration
- Accurate control, even in the very high end
- Flax sandwich cone: controlled and articulated bass, natural and detailed lower mid-range and upper mid-range registers
- Threads for ceilling and wall mounts (fastening accessories not supplied)

System		SHAPE 50		
Frequency response (±3dB)		50Hz - 35kHz		
Maximum SPL (musical signal)		106dB SPL (peak @ 1m)		
Electronic section				
Inputs / Impedance	Туре	XLR: balanced 10kΩ		
	Connectors	RCA: unbalanced 10kΩ with sensitivity compensation		
Midrange and low frequency amplifier		60W, Class AB		
High frequency amplifier		25W, Class AB		
Automatic standby	Standby on	After approximately 30 minutes with no signal		
	Standby off	Signal detection > 3 mV		
Electrical supply	Voltages	220 - 240V (T800mAL / 250V fuse) or 100 - 120V (T1.6AL/250V fuse)		
	Connection	IEC plug and detachable power cord		
Settings	High pass filter	Adjustable Full-range 45 / 60 / 90Hz		
	Bass (0 - 250Hz)	Adjustable, ±6dB		
	Midrange / Bass (160Hz, Q=1)	Adjustable, ±3dB		

Settings	High (4.5 - 35kHz)	Adjustable, ±3dB
3	Power On / Power Off	On / Off switch on rear panel
Standby consumption		< 0.5W
Displays and controls		LED for power On / Off and standby
Transducers		
Woofer		5" (13cm) Flax Cone
Tweeter		1" (25mm) 'M' profile Aluminum-Magnesium
Cabinet		
Construction		0.6" (15mm) MDF
Finish		Vinyl, real walnut and black painting
Dimensions with four rubber feet (H x W x D)		12.3 x 7.5 x 9.5" (312 x 191 x 242mm)
Weight		14.3lbs (6.5kg)

SHAPE 50

Recommended mounting kits

SHAPE 50

Wall mount	K&M® Fixing kit 24471 + K&M® 24359 adapter
Ceiling mount	K&M* Fixing kit 24496 + K&M* 24359 adapter
Table stand / Microphone stand	K&M* Fixing kit 232





