

LITTORA 1000 ICW SUB10

Product sheet

This subwoofer is the perfect partner in any system, offering power and dynamics, even at high volumes. The more there are, the more the effect is increased. Its very shallow mounting depth and its 10-inch (25.4cm) diameter make the product easy to conceal within a system. Like a dive watch, it has been rigorously developed to perfectly suit being used in extreme conditions, such as yachting or for outdoor or indoor use at home. This speaker driver is characterised by excellence and versatility. The power and refinement of the Focal sound in all conditions, no compromise.



Technical specifications

| Type of speaker | LITTORA 1000 ICW SUB10 |
|-----------------------------|---|
| Diameter | 10" |
| Recommended amplifier power | 100 - 300W |
| Nominal impedance | 8Ω |
| Minimal impedance | 4Ω at 85Hz |
| Sensitivity (2.83V/1m) | 90dB |
| Frequency response | 25Hz - 500Hz |
| Closed box volume 1, F -3dB | 35L - 32Hz |
| Closed box volume 2, F -3dB | 22L - 36Hz |
| Free air, F -3dB | 30Hz |
| IP certification | IP65 (ASTMB117) |
| Grille | Aluminium ready-to-paint |
| UV resistance | Yes (ASTMG53) |
| Operating temperatures | -25°C to 90°C |
| Number of mounting points | 8 |
| Connector | Etanche DT06-2S |
| Mounting depth | 4 ⁷ / ₈ " (123mm) |
| Certifications | ROHS, ROHS 2, ROHS CHINE, REACH |

Key points

- High-end sound and excellent power handling
- Developed in France
- Certified IP65 waterproofing
- Ready-to-paint white aluminium grille for limitless customisation
- Shallow mounting depth

Size (mm)

